

G-2020 | G-2023 | G-2323

SMOOTH FINISH STEEL
THICKNESS: 1 3/4"

POLYURETHANE SANDWICH DOOR
R-16 INSULATION



G-2023 doors, 10' x 10' and 12' x 12', Tex White

FEATURES AND BENEFITS


A HIGH-PRESSURE INJECTED POLYURETHANE

- Stronger and more energy-efficient insulation
- Solidly bonded to the steel sheets providing a section that is resistant to flexion.

B SMOOTH STEEL FINISH

- 23-gauge or 20-gauge steel, provides a bending resistance 15% greater than 26-gauge steel, for better resistance to impact and vandalism.
- Highly corrosion-resistant with galvanized steel having a minimum of G60 zinc coating (180 g/m²).


C INTERLOK™ TRIPLE-CONTACT JOINTS

- Sections are strengthened by 2 steel walls joined together with mechanical interlocking joints which are more solid than just two bonded walls.
- Their mechanical thermal breaks are more efficient compared to thermal breaks made with glue.
- Triple-contact joints provide 2 times more weathertightness than those of the competition. 

D METAL REINFORCEMENT PLATES



- Provide stronger fastening for hinges and struts. These 14-gauge plates are 2 times thicker than 20-gauge plates used by other manufacturers.

E WOOD END BLOCKS

- Provide a thermal break that is more effective than steel end caps which form a thermal bridge. 
- As structural elements of the sections, the kiln-dried pine wood end blocks are installed at the outer ends of the section. They are stronger than insulation covered with a steel cap.

F LAG SCREW SYSTEM

- Provides much better fastening of the end hinges. The lag screws engage 8 threads into the wood, compared to a self-tapping screw going through a steel end cap engaging only about 2 or 3 threads.



PANEL CONSTRUCTION


- 1 **Steel walls**
 - G60 **hot-dipped galvanized steel** with five coats of protective finish.
 - G-2020:** 20-gauge exterior and interior steel skins
 - G-2023:** 20-gauge exterior and 23-gauge interior steel skins
 - G-2323:** 23-gauge exterior and interior steel skins
 - Baked-on **polyester paint**. Can be repainted.
 - Smooth finish on both sides of the door.
 - Same quality of corrosion-resistant steel for interior and exterior faces
- 2 **1 3/4" (44.5 mm) insulated door** with high-pressure injected **polyurethane foam** ensuring a high thermal-resistance rating of **R-16** (RSI 2.8 or k= 0.357 W/m²K) and the solidity of a composite material.
- 3 **InterLok™ joints** between each section:
 - **Mechanical joints** ensure stronger sections with walls of each panel mechanically interlocked (not only bonded by the polyurethane).
 - **Mechanical thermal break** avoids heat transfer between the interior and exterior walls of each section.
 - **Triple-contact joint** prevents air infiltration.
- 4 **U-shaped tubular bottom weatherstripping** made of thermoplastic elastomer (TPE) ensures the weathertightness of the threshold. Remains flexible and watertight during cold weather, to -62°F (-52°C).
- 5 **Wood end blocks** made of kiln-dried pine (grade 4). With our lag screw system, they ensure better fastening of end hinges. They also provide a thermal break which prevents thermal bridging.
- 6 14-gauge steel **reinforcement plates** placed inside the door for solidly attaching hinges and struts.

Door weight: **G-2020:** 3.35 lb/ft² (16.3 kg/m²)
G-2023: 3.15 lb/ft² (15.4 kg/m²)
G-2323: 2.85 lb/ft² (13.9 kg/m²)



Interior view

COLOR




Tex White

Color may slightly vary from image

MODELS



4 Grooves



2 Grooves

SIZES

Widths In 1" (25 mm) increments	From 5' to 24'2" (1.5 m to 7.4 m)	
Heights G-2020 / G-2023' In 3" (76 mm) increments G-2323 In 1" (25 mm) increments	From 6' to 24' (1.8 m to 7.3 m)	¹ Not available in 75", 78" and 81" high.

WINDOWS



Standard Windows
21" x 13" (533 mm x 330 mm)
Glass: see details on page 5
Colors: White



Oval Windows
Polycarbonate only
26" x 13" (660 mm x 330 mm)
Color: Black



G-4400 Sections (Full Vision)
Colors: White, Black and Anodized
See details on pages 10 and 11

HARDWARE

Steel tracks: • 2" (50 mm), 13-gauge or 14-gauge
• 3" (76 mm), 12-gauge

See details on page 20.

WARRANTIES (LIMITED)

10 years against any perforation of steel due to rust
 10 years on the wood end blocks against cracking and rot
 10 years against delamination of the steel skin from the polyurethane foam
 1 year on other door components
 10 years against seal defects on Standard windows